



NAMEPLATE
MODEL, SERIAL #,
AND CONVERSION CHART

14 31/64 " [367.98mm] EFFECTIVE LENGTH

9/16 " [14.40mm]

11/64 " [4.53mm]

23/64 " [8.99mm]

1 31/64 " [37.55mm]

3/8 SQ.DR.

Models				
Model	Drive Size	Drive Type	Capacity	Graduation Steps
C2FR50F	3/8	Flex Ratchet	10-50 lb. ft.	1 lb. ft.
C2FR600H		Flex Ratchet	120 - 600 lb. in.	10 lb. in.
C2FR100F		Flex Ratchet	20-100 lb. ft.	2 lb. ft.
C2R100F		Fixed Ratchet	20-100 lb. ft.	2 lb. ft.
C2FR68N		Flex Ratchet	14-68 N•m	2 N•m
C2FR135N		Flex Ratchet	25-135 N•m	5 N•m
C2FR14M		Flex Ratchet	3-14 Kg•m	0.2 Kg•m

Specifications:
 Overall Length: 17-5/64"
 Effective Length: 14-31/64"
 Width: 1-3/16"
 Head Height (without square): 9/16"
 Weight: 1.48 lbs.
 (w/plastic case): 2.35 lbs.
 Finish: Nickel / Chrome
 Ratchet Service Kit: R22BF-RK
 Meets or Exceeds the following Specifications: GGG-W-686C, ANSI B107.14M

Accurate within 4% of reading from 20% of full scale to full scale.

NOTE: "TQR" SERIES ARE PROVIDED WITH A NON-FLEX RATCHET.

THE DATA, DRAWINGS, AND INFORMATION CONTAINED ON THIS DOCUMENT IS CONFIDENTIAL AND THE SOLE PROPERTY OF SNAP-ON TORQOMETER SERVICE AND MAYNOT BE REPRODUCED, USED, OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION OF AN OFFICER OF SNAP-ON TORQOMETER SERVICE.

SCALE _____ DR L. COOK APP _____
 PKG CUSTOMER DATE 6/24/04 CADD# _____



P.O. Box 1306
 Des Plaines, IL 60016
 WEB: www.torqwrench.com
 FAX: 847-824-7629
 OFFICE: (847) 824-8456
 (866) TWRENCH (897-3624)

CUSTOMER PRINT

DESCRIPTION
 ADJUSTABLE CLICK
 TYPE TORQUE WRENCH

PART NUMBER
 C2FR & C2R Series